



RECOMMENDED LAYOUT  
FOR .062 THICK P.C. BOARD

1. PARTS COMPLY WITH TE SOLDERABILITY  
SPEC. NO. 109-11-3

2. CONTACT IS PLATED OVERALL WITH .000050 NICKEL,  
THEN .000030 GOLD OVER CONTACT LENGTH INDICATED  
AND TIN PLATED ON SOLDER TAIL END.

SUPERSEDED BY  
2-1586546-0

1-380999-0	NYLON	NATURAL	COPPER ALLOY GOLD	△
1-380999-0	NYLON -	NATURAL	COPPER ALLOY PRE-TIN	
ASSEMBLY NO.	HSG. MATL.	COLOR	PIN MATL. FINISH	

REVISION RECORD				NUMBER		DWG. SIZE		NUMBER		NAME		REMARKS		ITEM NO.	
U3	REVISED PER ECR-18-008156	JB	DZ	15JUN	2018										
U2	REVISED PER ECR-13-008342	AV	RP	12NOV	13										
U1	REVISED PER ECO-11-005294	RK	HMR	12APR	11										
LTR	REVISION RECORD	DR	CHK	D/JC											

  

REQUIRED PER ASSEMBLY		MATERIAL AND FINISH		CUSTOMER COPY REFERENCE ONLY	
DR	<i>Dr. Hoffman</i> 3/20/13	SEE TABLE	TE Connectivity		
CHK	<i>LMH</i> 3/20/13				
DE	<i>Shuttle</i> 4-3-73	WIRE - RANGE - INSULATION	TYPE PIN HEADER		
APP	<i>Shuttle</i> 4-3-73	TOLERANCE EXCEPT AS NOTED	SCALE	LOC CM	NO B 380999
		NAME 6 CIRCUIT MATE-N-LOK P.C. BOARD HEADER			