





10 9 8 7 6 5 4 3 2 1




RECOMMENDER PCB LAYOUT

P/N	DIM	A	B	C
47053-1000		3.50	13.50	7.50
47053-3000		4.00	13.84	7.34



NOTES:

1. MATERIAL: HOUSING: NYLON, UL94V-0. COLOR: IVORY.
PIN: COPPER ALLOY.
2. PLATING: 0.00254 MIN. MATTE TIN OVER 0.00127 MIN. NICKEL
3. PIN PUSH OUT FORCE: 0.91Kgf.
4. PARTS CONFORM TO PRODUCT SPEC PS-47053-001.
5. SOLDERABILITY: PER SMES-152
6. THIS PART CONFORMS TO CLASS B REQUIREMENTS OF COSMETIC SPECIFICATION PS-45499-002



PLATING, ADD DIM C EC NO: UCP2012-1821 DRAWN:MSTR0H 2011/12/22 CHKD:MK/PPER 2012/01/03 APPR:FSM/TH 2012/02/02	QUALITY SYMBOLS <div>▽_A=0</div> <div>▽_B=0</div> <div>▽_C=0</div>	DESCRIPTION	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	
				MM ONLY		1:1	METRIC		
						TITLE		4 PIN HEADER HOUSING WITH FRICTION LOCK	
						MOLEX MOLEX INCORPORATED			
						SD-47053-001		1 OF 1	
REV	C	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	SIZE B	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION					

9 8 7 6 5 4 3 2 1